California Department of Public Health Product WorkSheet					
Manufacturing Company Information	Product Brand:	Everpure			
Pentair Residential Filtration, LLC		3			
5730 N. Glen Park Road	Product Model:	BW-500 Drinking Water system			
Milwaukee, Wisconsin 53209	CDPH registration #	12-2144			
Phone: (262)-238-4400	Replacement Cartridge	BW-500			

Operating Parameters	SI Units	Metric Units
Service Flow Rate	0.5 gpm	1.9 lpm
System Capacity	480 gallons	1816 L
Pressure	10-125 psi	0.7 - 8.7 Kg/cm <sup>2</sup>
Temperature	35-100°F	1.6-37.8°C

Website: www.pentairaqua.com

Everpure BW-500 Drinking Water system Performance Data Sheet					
Contaminat Reduction Claims	Challenge Concentration	Maximum Permissible Product Water Concentration	Reduction Requirements	Reduction Average	
Cyst	Minimum 50,000/mL		≥ 99.95%	99.99%	
Lead (pH 6.5)	0.15 mg/L ± 10%	0.010 mg/L		99.30%	
Lead (pH 8.5)	0.15 mg/L ± 10%	0.010 mg/L		99.20%	
Total Trihalomethanes (TTHM)	0.300 mg/L ± 10%	0.015 mg/L		97.50%	

Note: The manufacturer is required to re-test the product every 5 years for material safety, structural integrity and all performance claims made. Any change to the product must be submitted to the certification agency for a technical review. Testing may be required sooner based on the technical review.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Note: The system must be installed and maintained according to manufacturer's recommendations, including replacement of filter cartridges. The contaminants or other substances removed or reduced by this system are not necessarily in your water. Please see Product Installation manual for details.